

UEL Series

select	Inquiry	No.		Dimensions (mm)										Weight (kg)	Basic Load Rating[N]		Speed Limit (r/min)	Eccentric Sleeve Code
		新	旧	d	D	B	B1	C	S	D1	B2	G	ds		Cr	Cor		
UEL311	390611	55	120	55.8	73.0	34	27.8	82	22.2	9.0	M12x1.25	2.34	55.05	41.91	1400	E311		
UEL310	390610	50	110	49.4	66.6	32	24.6	76	22.2	9.0	M12x1.25	1.86	47.58	35.71	1700	E310		
UEL308	390608	40	90	41.5	57.1	27	19.8	63.5	20.6	8.1	M10x1.0	1.08	31.35	22.38	2000	E308		
UEL306	390606	30	72	36.5	50.0	23	17.5	49	17.5	6.5	M8x1.0	0.69	20.77	14.17	2600	E306		
UEL205	390505	25	52	34.9	44.4	17	17.5	38.1	13.5	4.8	M6x1.0	0.28	10.78	6.98	3400	E205		
UEL206	390506	30	62	36.5	48.4	19	18.3	44.5	15.9	6.0	M8x1.0	0.4	14.97	10.04	2800	E206		
UEL207	390507	35	72	37.6	51.1	20	18.8	55.6	17.5	6.8	M8x1.0	0.61	19.75	13.67	2400	E207		
UEL208	390508	40	80	42.8	56.3	21	21.4	60.3	18.3	6.8	M8x1.0	0.72	22.71	15.94	2200	E208		
UEL209	390509	45	85	42.8	56.3	22	21.4	63.5	18.3	6.8	M8x1.0	0.81	24.6	17.71	1900	E209		
UEL210	390510	50	90	49.2	62.7	24	24.6	69.9	18.3	7	M10x1.0	0.98	26.98	19.84	1800	E210		
UEL211	390511	55	100	55.5	71.4	25	27.8	76.2	20.7	7.0	M10x1.0	1.3	33.37	25.11	1600	E211		
UEL212	390512	60	110	61.9	77.8	27	31	84.2	22.3	8.0	M10x1.0	1.78	36.74	27.97	1500	E212		
UEL213	390513	65	120	69.2	85.7	28	34.1	86.0	23.5	8.5	M12x1.25	2.48	44.01	34.18	1400	E213		
UEL214	390514	70	125	69.2	85.7	29	34.1	90.0	23.5	8.5	M12x1.25	2.50	46.79	37.59	1300	E214		
UEL215	390515	75	130	76.6	92	30	37.3	102.0	23.5	8.5	M12x1.25	2.86	50.85	41.26	1200	E215		
UEL216	390516	80	140	70.0	92	33	33.3	110	30.0	11.0	M12x1.25	3.30	55.04	45.09	1100	E216		
UEL218	390518	90	160	80	100	37	39.7	115	30.0	12	M12x1.25	4.8	73.83	60.76	950	E218		

Page : 1/1