

Inch Tapered Roller Bearing

Bearing No.	Boundary dimensions[mm]						Basic load ratings(kN)		
	d	B	R	D	C	r	T	Dynamic(Cr)	Static(Cor)
M249747/710	257,175	358,775	71,438	842	1760	156	1200	1700	20,5
38880/38820	263,525	325,438	28,575	220	550	48	1300	1800	53,0
L555249/210	292,100	374,650	47,625	501	1140	98	1100	1600	12,0
L555249/210/VE174	292,100	374,650	47,625	501	1140	98	1100	1600	12,0
L357049/010/VE174	304,800	393,700	50,800	528	1220	104	1000	1500	14,5
LM361649A/610	343,154	450,850	66,675	935	2200	180	900	1300	28,0
L865547/512	381,000	479,425	49,250	594	1500	120	800	1200	20,0
HM266449/410	384,175	546,100	104,775	1870	4150	320	750	1100	77,0
LL566848/810/HA1	403,225	460,375	28,575	246	765	58,5	800	1200	6,70
LM567949/910/HA1	406,400	549,275	85,725	1380	3050	236	700	1000	53,5
LM770949/910	457,200	603,250	85,725	1450	3400	265	630	950	61,5
LM772748/710/HA1	488,950	634,873	84,183	1450	3650	265	600	850	63,5
EE243196/250/HA2	498,475	634,873	80,962	1470	3650	270	600	850	59,5
EE843220/290	558,800	736,600	88,108	1830	4150	305	500	750	92,5
LM377449/410	558,800	736,600	104,775	2330	5700	405	500	750	115
EE649240/310	609,600	787,400	93,662	2160	5300	380	450	670	110
EE649240AX/310	609,600	787,400	93,662	2160	5300	380	450	670	110
LM283649/610/HA1	749,300	990,600	159,500	4570	12000	750	340	500	330
L183448/410	760,000	889,000	88,900	1870	5850	380	360	530	94,0
LL483449/418	762,000	889,000	69,850	1230	3800	255	380	560	66,5
L183449/410	762,000	889,000	88,900	1870	5850	380	360	530	94,0
EE763330/410	838,200	1041,400	93,662	1900	4800	320	320	460	160