

英制圆锥滚子轴承系列

INCH TAPERED ROLLER BEARING

轴承型号/Bearing Model		轴承尺寸(mm)/Dimensions							重量(Kg)
内圈	外圈	d	D	T	B	C	Rmin	rmin	Weight
335	332A	34.925	80	24.175	22.403	21	0.8	2.3	0.56
28137	28317	34.925	80.035	21.433	20.940	15.875	1.5	1.5	0.49
27875	27820	34.925	80.035	24.608	23.698	18.512	0.8	1.5	0.59
3379	3339	34.925	80.035	29.37	30.391	23.812	3.5	1.5	0.71
335	3320	34.925	80.167	26.988	22.403	23.812	0.8	3.3	0.59
3379	3320	34.925	80.167	29.367	30.391	23.812	3.5	3.3	0.71
02877	02831	34.925	80.962	22.225	22.225	17.462	3.5	0.8	0.55
3379	3329	34.925	81.755	29.37	30.391	23.812	3.5	3.3	0.75
3379	3328	34.925	84.138	29.37	30.391	23.812	3.5	3.3	0.8
3872	3821	34.925	85.725	30.162	30.162	23.812	3.5	1.3	0.9
3872A	3820	34.925	85.725	30.162	30.162	23.812	0.8	3.3	0.89
3872	3820	34.925	85.725	30.162	30.162	23.812	3.5	3.3	0.89
3581	3525	34.925	87.312	30.162	30.886	23.812	3.5	3.3	0.92
417	414	34.925	88.5	26.988	29.083	22.225	0.8	1.5	0.88
4368	4335	34.925	90.488	39.688	40.386	33.338	3.5	3.3	1.36
449	432	34.925	95.25	27.783	29.9	22.225	0.8	2.3	1.08
19138	19267X	34.976	68	16.019	16.520	12.000	1.5	1.5	0.26
19138	19268	34.976	68.262	15.875	16.520	11.908	1.5	1.5	0.26
14139	14274	34.976	69.012	19.845	19.583	15.875	1.3	3.3	0.32
14139	14276	34.976	69.012	19.845	19.583	15.875	1.3	1.3	0.32
14139	14282	34.976	71.996	19.002	19.583	15.032	1.3	1.5	0.35
19138	19283	34.976	72	17.018	16.520	14.288	1.5	1.5	0.32
14139	14283	34.976	72.085	22.385	19.583	18.415	1.3	2.3	0.4
28138	28300X	34.976	76.2	20.625	20.94	15.494	1.5	1.5	0.43
28138	28315	34.976	80	21.005	20.940	15.875	1.5	1.5	0.49
L68149	L68110	34.987	59.131	15.875	16.764	11.938	3.5	1.3	0.17
L68149	L68111	34.987	59.975	15.875	16.764	11.938	3.5	1.3	0.17
LM78349	LM78310A	34.987	61.973	16.7	17.000	13.600	3.5	1.5	0.19
LM78349A	LM78310A	34.987	61.973	16.701	17	13.6	1.5	1.5	0.2
LM78349	LM78310C	34.987	61.973	18.001	17	15	3.5	1.5	0.2
LM78349A	LM78310C	34.987	61.973	18.001	17	15	1.5	1.5	0.21
M38547	M38511	34.987	65.987	20.638	20.638	16.670	3.5	2.3	0.30
JS-3549A	JS-3510	35	70	24	23.5	19	2.0	1.5	0.41
19138X	19283	35	72	17.018	16.520	14.288	2	1.5	0.32
19138X	19283X	35	72	17.018	16.520	14.288	2.0	2.0	0.32
23691	23620	35	73.025	26.988	26.975	22.225	3.5	1.5	0.52
23691	23621	35	73.025	26.988	26.975	22.225	3.5	0.8	0.52
14139X	14274-S	35	75.311	19.845	19.583	15.875	3.5	3.3	0.40
26883	26822	35	79.375	23.812	25.400	19.050	0.8	0.8	0.60
339	332	35	80	21	22.403	17.826	0.8	1.3	0.52
26883	26824	35	80	23.813	25.4	19.05	0.8	1.3	0.62
26883	26820	35	80.167	25.4	25.4	20.638	0.8	3.3	0.63

英制圆锥滚子轴承系列

INCH TAPERED ROLLER BEARING

轴承型号/Bearing Model		轴承尺寸(mm)/Dimensions							重量(Kg)
内圈	外圈	d	D	T	B	C	Rmin	rmin	Weight
3480	3422	35	80.167	29.37	29.771	23.812	1.5	3.3	0.72
421	412A	35	82.55	28.575	29.083	23.812	0.8	1.5	0.76
421	414	35	88.5	26.988	29.083	22.225	0.8	1.5	0.88
2880	2820	35.306	73.025	22.225	23.812	17.462	3.5	3.3	0.42
HM88648	HM88610	35.717	72.233	25.4	25.4	19.842	3.5	2.3	0.47
2794	2735X	36.487	73.025	23.812	25.654	19.05	3.5	0.8	0.47
25880	25821	36.487	73.025	23.812	24.608	19.050	1.5	0.8	0.46
2780	2735X	36.487	73.025	23.812	25.654	19.050	1.5	0.8	0.47
25880	25820	36.487	73.025	23.812	24.608	19.05	1.5	2.3	0.45
2780	2736	36.487	74.612	23.812	25.654	19.05	1.5	0.8	0.5
2794	2720	36.487	76.2	23.812	25.654	19.050	3.5	3.3	0.52
2780	2720	36.487	76.2	23.812	25.654	19.05	1.5	3.3	0.52
2780	2729	36.487	76.2	23.812	25.654	19.050	1.5	0.8	0.53
2780	2731	36.487	79.375	23.812	25.654	19.050	1.5	3.3	0.58
19143	19268	36.512	68.262	15.875	16.52	11.908	1.5	1.5	0.25
13682	13621	36.512	69.012	19.05	19.05	15.083	3.5	2.3	0.29
19143	19283X	36.512	72	17.018	16.52	14.288	1.5	2.0	0.31
19143	19283	36.512	72	17.018	16.520	14.288	1.5	1.5	0.31
16143	16282	36.512	72	19	20.638	14.237	3.5	1.5	0.34
16143	16284	36.512	72.238	20.638	20.638	15.875	3.5	1.3	0.36
31597	31521	36.512	76.2	29.37	28.575	23.812	3.5	1.3	0.6
31597	31520	36.512	76.2	29.37	28.575	23.812	3.5	3.3	0.59
HM89449	HM89410	36.512	76.2	29.37	28.575	23.020	3.5	3.3	0.62
HM89449	HM89411	36.512	76.2	29.37	28.575	23.02	3.5	0.8	0.63
HM89448	HM89410	36.512	76.2	29.37	28.575	23.020	0.8	3.3	0.62
3479	3420	36.512	79.375	29.37	29.771	23.812	0.8	3.3	0.68
HM89249	HM89210	36.512	79.375	29.37	28.829	22.664	3.5	3.3	0.7
26877	26824	36.512	80	23.812	25.400	19.050	0.8	1.3	0.60
26877	26820	36.512	80.167	25.4	25.400	20.638	0.8	3.3	0.61
3479	3422	36.512	80.167	29.37	29.771	23.812	0.8	3.3	0.70
25570	25520	36.512	82.931	23.812	25.400	19.050	3.5	0.8	0.66
3878	3820	36.512	85.725	30.162	30.162	23.812	0.8	3.3	0.87
44143	44348	36.512	88.5	25.4	23.698	17.462	2.3	1.5	0.73
46143	46368	36.512	93.662	31.75	31.750	26.195	1.5	3.3	1.15
JL69349	JL69310	38	63	17	17.000	13.500	0.0	1.3	0.20
JL69349A	JL69310	38	63	17	17	13.5	1.3	1.3	0.2
JL69348	JL69310	38	63	17	17	13.5	3.3	1.3	0.20
JL69349X	JL69310	38	63	17	17	13.5	2.3	1.3	0.20
19149X	19267X	38	68	16.02	16.520	12	2	1.5	0.24
13889	13830	38.1	63.5	12.7	11.908	9.525	1.5	0.8	0.14
13889	13836	38.1	65.088	12.7	11.908	9.525	1.5	0.8	0.16
LM29749	LM29710	38.1	65.088	18.034	18.288	13.97	2.3	1.3	0.24

英制圆锥滚子轴承系列

INCH TAPERED ROLLER BEARING

轴承型号/Bearing Model		轴承尺寸(mm)/Dimensions							重量(Kg)
内圈	外圈	d	D	T	B	C	Rmin	rmin	Weight
LM29748	LM29710	38.1	65.088	18.034	18.288	13.97	3.5	1.3	0.23
LM29749	LM29711	38.1	65.088	19.812	18.288	15.748	2.3	1.3	0.25
19150	19268	38.1	68.262	15.875	16.52	11.908	1.5	1.5	0.24
19150	19269	38.1	68.262	19.997	16.520	16.300	1.5	1.5	0.28
13685	13621	38.1	69.012	19.05	19.05	15.083	3.5	2.3	0.28
13685A	13621	38.1	69.012	19.05	19.05	15.083	0.8	2.3	0.29
13685	13620	38.1	69.012	19.05	19.050	15.083	3.5	0.8	0.28
13687	13621	38.1	69.012	19.05	19.05	15.083	2.0	2.3	0.28
13687	13620	38.1	69.012	19.05	19.05	15.083	2	0.8	0.28
13685A	13620	38.1	69.012	19.05	19.05	15.083	0.8	0.8	0.29
13686	13621	38.1	69.012	26.195	26.195	15.083	1.5	2.3	0.35
13686	13620	38.1	69.012	26.195	26.195	15.083	1.5	0.8	0.35
13685	13624	38.1	69.969	21.996	19.05	18.029	3.5	1.5	0.33
13687	13624	38.1	69.969	21.996	19.050	18.029	2.0	1.5	0.33
19150	19281	38.1	71.438	15.875	16.520	11.908	1.5	1.0	0.28
19150	19283	38.1	72	17.018	16.52	14.288	1.5	1.5	0.30
16150	16282	38.1	72	19	20.638	14.237	3.5	1.5	0.33
16150	16284	38.1	72.238	20.638	20.638	15.875	3.5	1.3	0.35
16150	16283	38.1	72.238	23.812	20.638	19.05	3.5	2.3	0.39
2788	2735X	38.1	73.025	23.812	25.654	19.05	3.5	0.8	0.45
2788A	2735X	38.1	73.025	23.812	25.654	19.05	1.5	0.8	0.45
2776	2735X	38.1	73.025	23.812	25.654	19.05	4.3	0.8	0.45
2788A	2736	38.1	74.612	23.812	25.654	19.050	1.5	0.8	0.48
28150	28300X	38.1	76.2	20.625	20.94	15.494	1.5	1.5	0.40
28151	28300	38.1	76.2	20.638	20.940	15.507	3.5	1.3	0.39
28150	28300	38.1	76.2	20.638	20.94	15.507	1.5	1.3	0.40
2788	2720	38.1	76.2	23.812	25.654	19.05	3.5	3.3	0.5
2788	2729X	38.1	76.2	23.812	25.654	19.050	3.5	1.5	0.51
2776	2720	38.1	76.2	23.812	25.654	19.05	4.3	3.3	0.5
2788A	2720	38.1	76.2	23.812	25.654	19.05	1.5	3.3	0.5
2788	2729	38.1	76.2	23.812	25.654	19.05	3.5	0.8	0.51
2777	2720	38.1	76.2	23.812	25.654	19.050	5.5	3.3	0.49
2788A	2729	38.1	76.2	23.812	25.654	19.05	1.5	0.8	0.51
26878	26823	38.1	76.2	25.4	25.400	20.638	0.8	1.5	0.52
26878	26822	38.1	79.375	23.812	25.400	19.050	0.8	0.8	0.56
2788	2734	38.1	79.375	25.4	25.654	20.638	3.5	3.3	0.58
2776	2734	38.1	79.375	25.4	25.654	20.638	4.3	3.3	0.58
3490	3420	38.1	79.375	29.37	29.771	23.812	3.5	3.3	0.65
3387	3325	38.1	79.975	29.37	30.391	23.812	0.8	3.3	0.67
28150	28315A	38.1	80	21.006	20.940	15.875	1.5	2.0	0.46
26878	26824	38.1	80	23.812	25.4	19.05	0.8	1.3	0.58
27880	27820	38.1	80.035	24.608	23.698	18.512	0.8	1.5	0.56

英制圆锥滚子轴承系列

INCH TAPERED ROLLER BEARING

轴承型号/Bearing Model		轴承尺寸(mm)/Dimensions							重量(Kg)
内圈	外圈	d	D	T	B	C	Rmin	rmin	Weight
27881	27820	38.1	80.035	24.608	23.698	18.512	3.5	1.5	0.55
3387	3339	38.1	80.035	29.37	30.391	23.812	0.8	1.5	0.67
26878	26820	38.1	80.167	25.4	25.4	20.638	0.8	3.3	0.59
26878	26830	38.1	80.167	25.4	25.400	20.638	0.8	0.8	0.6
347	3320	38.1	80.167	26.988	22.403	23.812	3.5	3.3	0.55
3381	3331	38.1	80.167	29.37	30.391	23.812	3.5	0.8	0.68
3381	3320	38.1	80.167	29.37	30.391	23.812	3.5	3.3	0.67
3387	3320	38.1	80.167	29.37	30.391	23.812	0.8	3.3	0.67
3381	3329	38.1	81.755	29.37	30.391	23.812	3.5	3.3	0.71
3387	3329	38.1	81.755	29.37	30.391	23.812	0.8	3.3	0.71
HM801346	HM801310	38.1	82.55	29.37	28.575	23.020	0.8	3.3	0.76
HM801346X	HM801310	38.1	82.55	29.37	28.575	23.02	2.3	3.3	0.76
HM801346	HM801311	38.1	82.55	29.37	28.575	23.020	0.8	0.8	0.77
25572	25520	38.1	82.931	23.812	25.4	19.050	0.8	0.8	0.65
25572	25526	38.1	85	23.812	25.4	19.05	0.8	2.3	0.69
3875	3820	38.1	85.725	30.162	30.162	23.812	0.8	3.3	0.85
3876	3821	38.1	85.725	30.162	30.162	23.812	3.5	1.3	0.85
3876	3820	38.1	85.725	30.162	30.162	23.812	3.5	3.3	0.84
3580	3525	38.1	87.312	30.162	30.886	23.812	1.5	3.3	0.88
3583	3525	38.1	87.312	30.162	30.886	23.812	3.5	3.3	0.87
44150	44348	38.1	88.5	25.4	23.698	17.462	2.3	1.5	0.71
418	414	38.1	88.5	26.988	29.083	22.225	3.5	1.5	0.83
418	414A	38.1	88.5	26.988	29.083	22.225	3.5	3.3	0.82
418	414X	38.1	88.9	26.988	29.083	22.225	3.5	0.8	0.84
4375	4335	38.1	90.488	39.688	40.386	33.338	1.5	3.3	1.31
49151	49368	38.1	93.662	31.75	31.75	25.4	0.8	3.3	1.09
440	432	38.1	95.25	27.782	29.9	22.225	0.8	2.3	1.04
444	432	38.1	95.25	27.783	29.900	22.225	3.5	2.3	1.03
33880	33821	38.1	95.25	27.783	28.575	22.225	3.5	2.3	1.05
53150	53375	38.1	95.25	30.958	28.3	20.638	1.5	0.8	1.01
53150	53387	38.1	98.425	30.958	28.3	20.638	1.5	0.8	1.09
525	522	38.1	101.6	34.925	36.068	26.988	3.5	3.3	1.48
525X	522	38.1	101.6	34.925	36.068	26.988	0.8	3.3	1.49
542	533A	38.1	103.188	38.1	36.957	30.162	3.5	1.5	1.65
455A	453A	38.1	107.95	27.783	29.317	22.225	3.5	0.8	1.43
542	532A	38.1	111.125	38.1	36.957	30.162	3.5	3.3	1.96
13890	13830	38.481	63.5	12.7	11.908	9.525	0.4	0.8	0.14
13890	13836	38.481	65.088	12.7	11.908	9.525	0.4	0.8	0.16
J16154	J16285	39	72.014	21.4	20.638	16.637	3.5	0.4	0.35
18587	18520	39.687	73.025	16.667	17.462	12.7	0.8	1.5	0.30
2789	2735X	39.687	73.025	23.812	25.654	19.05	3.5	0.8	0.43
M201047	M201011	39.687	73.025	25.654	22.098	21.336	0.8	2.3	0.44

英制圆锥滚子轴承系列

INCH TAPERED ROLLER BEARING

轴承型号/Bearing Model		轴承尺寸(mm)/Dimensions							重量(Kg)
内圈	外圈	d	D	T	B	C	Rmin	rmin	Weight
2789	2720	39.687	76.2	23.812	25.654	19.05	3.5	3.3	0.48
2789	2729	39.687	76.2	23.812	25.654	19.050	3.5	0.8	0.49
26881	26823	39.687	76.2	25.4	25.4	20.638	3.5	1.5	0.50
26880	26822	39.687	79.375	23.812	25.400	19.050	1.5	0.8	0.54
26881	26822	39.687	79.375	23.812	25.4	19.05	3.5	0.8	0.54
26880	26822A	39.687	79.375	23.812	25.4	19.05	1.5	2.3	0.54
3382	3325	39.688	79.975	29.37	30.391	23.812	3.5	3.3	0.65
3386	3325	39.688	79.975	29.37	30.391	23.812	0.8	3.3	0.65
26881	26824	39.687	80	23.812	25.4	19.05	3.5	1.3	0.56
3386	3339	39.688	80.035	29.37	30.391	23.812	0.8	1.5	0.65
26881	26820	39.687	80.167	25.4	25.400	20.638	3.5	3.3	0.57
26880	26830	39.687	80.167	25.4	25.4	20.638	1.5	0.8	0.58
26880	26820	39.687	80.167	25.4	25.4	20.638	1.5	3.3	0.57
26881	26830	39.687	80.167	25.4	25.400	20.638	3.5	0.8	0.58
26880	26821	39.687	80.167	29.37	25.400	24.608	1.5	3.3	0.63
3382	3331	39.688	80.167	29.37	30.391	23.812	3.5	0.8	0.66
3382	3320	39.688	80.167	29.37	30.391	23.812	3.5	3.3	0.65
3386	3331	39.688	80.167	29.37	30.391	23.812	0.8	0.8	0.66
3386	3320	39.688	80.167	29.37	30.391	23.812	0.8	3.3	0.65
3386	3328	39.688	84.138	29.37	30.391	23.812	0.8	3.3	0.74
3382	3328	39.688	84.138	29.37	30.391	23.812	3.5	3.3	0.74
44156	44348	39.687	88.5	25.4	23.698	17.462	2.3	1.5	0.69
44158	44348	39.687	88.5	25.4	23.698	17.462	3.5	1.5	0.69
620	612	39.687	120.65	41.275	41.275	31.75	0.8	3.3	2.53
28156	28300	39.98	76.2	19.347	19.65	15.507	2.3	1.3	0.37
28159	28300	39.98	76.2	20.638	20.94	15.507	3.5	1.3	0.37
28156	28317	39.98	80.035	20.142	19.65	15.875	2.3	1.5	0.43
HM204043	HM204010	39.987	90.975	32	32	26.5	1	3.5	1.02
28158	28300X	40	76.2	20.625	20.940	15.494	1.5	1.5	0.38
344A	332	40	80	21	22.403	17.826	0.8	1.3	0.47
28158	28315	40	80	21.005	20.94	15.875	1.5	1.5	0.44
28158	28315A	40	80	21.006	20.94	15.875	1.5	2	0.44
350	3520	40	84.138	26.988	21.692	23.812	4	3.3	0.61
350	354A	40	85	20.638	21.692	17.462	4	1.3	0.55
350	354X	40	85	20.638	21.692	17.462	4	1.5	0.55
357	354A	40	85	20.638	21.692	17.462	2.3	1.3	0.56
JF4049	JF4010	40	85	33	32.5	28	2.5	2	0.9
3879	3820	40	85.725	30.162	30.162	23.812	0.8	3.3	0.82
3582	3525	40	87.312	30.162	30.886	23.812	3.5	3.3	0.84
44157X	44348	40	88.5	24.765	23.063	17.462	2.3	1.5	0.68
420	414	40	88.5	26.988	29.083	22.225	3.5	1.5	0.80
420	414X	40	88.9	26.988	29.083	22.225	3.5	0.8	0.81

英制圆锥滚子轴承系列

INCH TAPERED ROLLER BEARING

轴承型号/Bearing Model		轴承尺寸(mm)/Dimensions							重量(Kg)
内圈	外圈	d	D	T	B	C	Rmin	rmin	Weight
350	352X	40	90	23	21.692	21.808	4.0	2.3	0.70
350	352	40	90.119	23	21.692	21.808	4	2.3	0.71
350A	352	40	90.119	23	21.692	21.808	0.8	2.3	0.72
357	352	40	90.119	23	21.692	21.808	2.3	2.3	0.72
442-S	432	40	95.25	27.783	29.9	22.225	3.5	2.3	1.00
543	532X	40	107.95	36.512	36.957	28.575	3.5	3.3	1.74
HM801349	HM801310	40.483	82.55	29.37	28.575	23.020	3.5	3.3	0.72
LM300849	LM300811	40.987	67.975	17.5	18	13.5	3.5	1.5	0.24
LM300848	LM300811	41.275	67.975	17.5	18	13.5	3.5	1.5	0.24
18590	18520	41.275	73.025	16.667	17.462	12.7	3.5	1.5	0.28
LM501349	LM501310	41.275	73.431	19.558	19.812	14.732	3.5	0.8	0.34
LM501349A	LM501310	41.275	73.431	19.558	19.812	14.732	0.8	0.8	0.33
LM501349	LM501314	41.275	73.431	21.43	19.812	16.604	3.5	0.8	0.36
LM501349	LM501311	41.275	73.431	23.012	19.812	18.186	3.5	2.3	0.37
11163	11300	41.275	76.2	18.009	17.384	14.288	0.8	1.5	0.34
11162	11300	41.275	76.2	18.009	17.384	14.288	1.5	1.5	0.34
24780	24722	41.275	76.2	22.225	23.02	17.462	3.5	3.3	0.42
24780	24720	41.275	76.2	22.225	23.020	17.462	3.5	0.8	0.43
24781	24720	41.275	76.2	22.225	23.02	17.462	0.8	0.8	0.43
24780	24721	41.275	76.2	25.4	23.02	20.638	3.5	2.3	0.47
24781	24721	41.275	76.2	25.4	23.02	20.638	0.8	2.3	0.47
26882	26822	41.275	79.375	23.812	25.400	19.050	3.5	0.8	0.52
26885	26822	41.275	79.375	23.812	25.400	19.050	0.8	0.8	0.52
11162	11315	41.275	80	18.009	17.384	14.288	1.5	1.5	0.39
342	332	41.275	80	21	22.403	17.826	3.5	1.3	0.45
336	332	41.275	80	21	22.403	17.826	0.8	1.3	0.46
3383	3339	41.275	80.035	29.37	30.391	23.812	3.5	1.5	0.62
26882	26820	41.275	80.167	25.4	25.400	20.638	3.5	3.3	0.55
336	3320	41.275	80.167	26.988	22.403	23.812	0.8	3.3	0.53
342	3320	41.275	80.167	26.988	22.403	23.812	3.5	3.3	0.52
26882	26821	41.275	80.167	29.37	25.400	24.608	3.5	3.3	0.61
3383	3329	41.275	81.755	29.37	30.391	23.812	3.5	3.3	0.66
22778	22721	41.275	82.55	26.195	26.988	20.638	3.5	0.8	0.64
M802048	M802011	41.275	82.55	26.543	25.654	20.193	3.5	3.3	0.62
M802047	M802011	41.275	82.55	26.543	25.654	20.193	0.8	3.3	0.63
3383	3328	41.275	84.138	29.37	30.391	23.812	3.5	3.3	0.71
3576	3520	41.275	84.138	30.162	30.886	23.812	0.8	3.3	0.75
3576	3530	41.275	84.138	30.162	30.886	23.812	0.8	0.8	0.76
3577	3530	41.275	84.138	30.162	30.886	23.812	3.5	0.8	0.75
3877	3820	41.275	85.725	30.162	30.162	23.812	3.5	3.3	0.80
3880	3820	41.275	85.725	30.162	30.162	23.812	0.8	3.3	0.80
3880	3821	41.275	85.725	30.162	30.162	23.812	0.8	1.3	0.81